coverguard®

TECHNICAL DATASHEET

DIN Filter P3 RD (DIRIN SERIES)

Ref. 6REF280

Cartridges DIN

P3 R



D

The +

P3 R. Universal DIN EN 148/1 / RD-40 thread.

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6REF280NSI	-		12

SALES PACKAGING

Hangable box

DESCRIPTION

Dust filter with special threaded linkage DIN EN148-1 / RD-40 for P3 R fine toxic dust, mist and aerosols. It works best when fitted with ARNASYS full mask (6FFD00) but can also be used on all masks equipped with UNIVERSAL THREAD DIN148-1 / RD-40, and especially EURMASK DIN (6EUR100NSI).
Container made of impact resistant and anti-scratch synthetic resin. Can be incinerated after use.
Boxe of 8 filters.

SECTORS

- Heavy & process industries
- Light Industries
- Infrastructure, building industry

APPLICATIONS

Toxic dusts, mists and fog, For regular and prolonged use in a dangerous environment: carpentry, wood industry, cement industry, metal cutting...

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57

TECHNICAL FEATURES

Shape	Universal filter
Weight	75 g
Specifications	P3 R
Main risk	Respiratory protection from aerosols, dusts, and fog
Features	P3 R Breathing resistance : * 30 l/min : 0,90 mbar. * 95 l/min : 3,10 mbar.
Service life	Can be used until abnormal breathing resistance and/or strange smell.

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE026AT2042**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy

CE EPI CAT. III

EN143:2000 / A1:2006 Particles filters

MAJ 21/02/2025

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57